


Universal Testing Type Accelerometer


DETAILS

Model AXXYD5/AXXE3 3-axis capacitive acceleration sensor with variable capacitive MEMS sensitive element. The AC excitation and modulation-demodulation circuitry contained within the internal internal circuitry of the sensor outputs an analog output voltage signal proportional to the acceleration. The sensitive element and circuitry are encapsulated within a titanium alloy housing with a 5/16-32 9-pin connector output and signal ground isolated from the housing.

Fig_1 Dimensions of AXXYD5/AXXE3



Fig_2 Typical Temperature Response



FEATURES

- Zero frequency voltage output type
- Low power consumption, low noise, high resolution
- Three-axis through-hole design, multiple ranges available
- Broadband response


TYPICAL APPLICATIONS

- Road spectrum testing
- Overload testing
- Foundation building structure testing
- Low frequency testing



AXXYD5/AXXE3

Fig_3 Typical Frequency Response



Specifications-AXXYD5/AXXYE3

MODEL NUMBER		UNIT	A03YD5/ A03YE3	A05YD5/ A05YE3	A06YD5/ A06YE3	A07YD5/ A07YE3	A09YD5/ A09YE3	A10YD5/ A10YE3	A11YD5/ A11YE3
PERFORMANCE									
Sensitivity ¹		mV/g	20	40	80	135	400	800	2000
		mV/(m/s²)	2	4	8	13.5	40	80	200
Range		g	±200	±100	±50	±30	±10	±5	±2
Non-Linearity (typ) ²		%	0.1						
Non-Linearity (max) ²		%	0.3						
Frequency Range	± 5%	Hz	0-2k	0-1.5k	0-1.5k	0-1.5k	0-1k	0-0.7k	0-0.5k
	±10%		-	-	-	-	-	-	-
Resonance Frequency ³		Hz	11k	8.5k	5.8k	4.2k	3.2k	1.9k	1.2k
Transverse Sensitivity		%	≤0.2						
Output Mode		-	Single-ended/Differential						
ELECTRICAL									
Excitation Voltage		V DC	6-30						
Full Range Voltage		V	±4						
Output Impedance		Ω	≤90						
ENVIRONMENTAL									
Sinusoidal Vibration Limit ⁴		g rms	5000	5000	5000	5000	5000	2000	2000
Shock Limit ⁴		g pk	5000	5000	5000	5000	5000	2000	2000
Temperature Range		°C	-55-125						
		°F	-67-257						
PHYSICAL									
Sealing		-	Laser welding IP68						
Sensing Element		-	MEMS Chip						
Housing Material		-	Titanium alloy						
Size	mm	22.60 Cube							
	in	0.890 Cube							
Electrical Connector		-	5/16-32 9-pin Side						
Mounting Thread		-	M5						
Weight ³	g	38							
	oz	1.340							

Additional Information

Note:

1. @ 160Hz, under the condition of 23 °C± 5 °C
2. JBT 6822-2018 7.12.1 Vibration Testing Method
3. Typical values
4. It refers to the mechanical structure of the sensor not being damaged in a non powered state, rather than in a working state

AXXYD5/AXXYE3

Supplied Accessories:

- Product Verification Report
- Install screws

COMPLIANCE WITH STANDARDS



LNS Intelligent Technology Co., Ltd

N0.3 Building
Qilu High-Tech District, Qihe,Dezhou
Shandong Province, China 251100
+86-534-2150417

International:
9620 NE Tanasbourne Dr Ste 300
Hillsboro, OR, USA 97124
+1-503-208-5512
info@lnsdynamics.com